


AVERY DENNISON MARKETING SPECIFICATION

HISTORY

THE SUBJECT MATTER DISCLOSED HEREIN EMBODIES PROPRIETARY INFORMATION WHICH IS THE CONFIDENTIAL PROPERTY OF THE AVERY DENNISON CO. NONE OF WHICH SHALL BE COPIED, REPRODUCED, DISCLOSED TO OTHERS, PUBLISHED OR USED IN WHOLE OR IN PART, FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS BEING MADE AVAILABLE WITHOUT THE EXPRESS ADVANCE WRITTEN PERMISSION OF A DULY AUTHORIZED AGENT OF THE COMPANY. THIS DOCUMENT IS THE PROPERTY OF THE AVERY DENNISON CO. AND IS TO BE RETURNED TO THE COMPANY ON DEMAND.

REV.	DATE	DESCRIPTION
C	08.03.18	UPDATES TO NEW FORMAT; ADDED -0 TO PART NUMBER; ADDED SPECIAL CHARACTERISTIC NOTE



NOTES:
1. Δ = INDICATES SPECIAL CHARACTERISTIC

9	Δ FLAMMABILITY:	HB RATED PER FMVSS302
10	Δ TENSILE STRENGTH:	222N / 50 lbf MIN.
	MOUNTING:	$\varnothing 8.0\text{mm} \pm .25$ HOLE AND M10 THREADED HOLE
	OPERATING TEMP RANGE:	-40 °F (-40 °C) TO 239 °F (115 °C) CONTINUOUS AND 257 °F (125 °C) AT MAXIMUM EXPOSURE
	WEIGHT:	1.8g
	BUNDLE DIAMETER:	$\varnothing 1.6\text{mm}$ [.06in] TO $\varnothing 44.5\text{mm}$ [1.75in]
	TOOL:	12001 - HAND TOOL 12500 - PNEUMATIC TOOL
	TOOL TENSION SETTING:	6 - 8
	PACKAGING:	500/BAG, 10 BAGS/MASTER

APPROVALS:

ENG. APPR.	<i>Daniel Gilbertson</i>	08.03.18
Q.A. APPR.	<i>Rick Estano</i>	08.03.18



FASTENER DIVISION
FITCHBURG, MA 01420 U.S.A.
TEL. 1-800-225-5913
FAX. 978-353-8157

SPECIFIED TOLERANCES ARE:

.XX \pm .03 INCHES	.X \pm .7 mm
.XXX \pm .010 INCHES	.XX \pm .25 mm
ANGULAR: $\pm 2^\circ$	

MATERIAL	NYLON 6/6, IMPACT MODIFIED, HEAT STAB.
COLOR	BLACK

DESCRIPTION	CURVE TIE, 8mm, 4 FLUTE, BLACK	
PART NO.	20094-0	REV. C