



AVERY DENNISON MARKETING SPECIFICATION

HISTORY

THE SUBJECT MATTER DISCLOSED HEREIN EMBODIES PROPRIETARY INFORMATION WHICH IS THE CONFIDENTIAL PROPERTY OF THE AVERY DENNISON CO. NONE OF WHICH SHALL BE COPIED, REPRODUCED, DISCLOSED TO OTHERS, PUBLISHED OR USED IN WHOLE OR IN PART, FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS BEING MADE AVAILABLE WITHOUT THE EXPRESS ADVANCE WRITTEN PERMISSION OF A DULY AUTHORIZED AGENT OF THE COMPANY. THIS DOCUMENT IS THE PROPERTY OF THE AVERY DENNISON CO. AND IS TO BE RETURNED TO THE COMPANY ON DEMAND.

REV.	DATE	DESCRIPTION
C	12/05/08	UPDATE OPERATING TEMP; AND APPLICABLE PANEL THICKNESS
D	08.03.18	UPDATES TO NEW FORMAT; ADDED -0 TO PART NUMBER; ADDED SPECIAL CHARACTERISTIC NOTE



ASSEMBLED VIEW

9	△ FLAMMABILITY RATING:	HB RATED PER FMVSS302
10	△ TENSILE STRENGTH:	222N/ 50 LBF MIN.
	MOUNTING:	Ø 6.60mm ± 0.25mm HOLE AND 6.35mm HEX HOLE. PANEL THICKNESS OF 0.7mm TO 7.0mm
	OPERATING TEMP RANGE:	-40°F (-40°C) TO 257°F (125°C)
	WEIGHT:	1.8g
	BUNDLE DIAMETER:	Ø 1.6mm [.06in] TO Ø 4.5mm [1.75in]
	INSTALLATION TOOL:	12001 - HAND TOOL 12500 - PNEUMATIC TOOL
	TOOL TENSION SETTING:	6 - 8
	PACKAGING:	500/BAG, 10 BAGS/MASTER

NOTES:

1. △ = INDICATES SPECIAL CHARACTERISTIC

APPROVALS:	ENG. APPR.	DATE
	<i>Daniel Gilbertson</i>	08.03.18
	<i>Rick Estano</i>	08.03.18

SPECIFIED TOLERANCES	MATERIAL
INCHES [mm]	NYLON 6/6, IMPACT MODIFIED, HEAT STAB.
.XX ± .03 .X ± .7	COLOR
.XXX ± .010 .XX ± .25	GRAY
ANGULAR: ± 2°	

AVERY DENNISON <small>FASTENER DIVISION FITCHBURG, MA 01420 U.S.A. TEL. 1-800-225-5913 FAX. 978-353-8157</small>	DESCRIPTION
	LOW INSERTION FIR TREE TIE
PART NO.	REV.
20105-0	D