


AVERY DENNISON MARKETING SPECIFICATION

HISTORY

REV.	DATE	DESCRIPTION
A	09-21-12	RELEASED

THE SUBJECT MATTER DISCLOSED HEREIN EMBODIES PROPRIETARY INFORMATION WHICH IS THE CONFIDENTIAL PROPERTY OF THE AVERY DENNISON CO. NONE OF WHICH SHALL BE COPIED, REPRODUCED, DISCLOSED TO OTHERS, PUBLISHED OR USED IN WHOLE OR IN PART, FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS BEING MADE AVAILABLE WITHOUT THE EXPRESS ADVANCE WRITTEN PERMISSION OF A DULY AUTHORIZED AGENT OF THE COMPANY. THIS DOCUMENT IS THE PROPERTY OF THE AVERY DENNISON CO. AND IS TO BE RETURNED TO THE COMPANY ON DEMAND.



MOUNTING:	M6 THREADED HOLE
TENSILE STRENGTH:	50 LBF / 222.4N MIN.
TEMPERATURE RANGE:	-40 °F (-40 °C) TO 239 °F (115 °C) CONTINUOUS AND 257 °F (125 °C) AT MAXIMUM EXPOSURE
WEIGHT:	2.35 GRAMS EACH
BUNDLE DIAMETER:	$\phi 1/4"$ (6.35MM) TO $\phi 1 - 7/8"$ (47.6MM)
INSTALLATION TOOL:	12001 - HAND TOOL 12500 - PNEUMATIC TOOL
TOOL TENSION SETTING:	6 - 8
PACKAGING:	500/BAG, 10 BAGS/MASTER

APPROVALS: ENG. APPR. *[Signature]* 10/3/12
Q.A. APPR. *[Signature]* 10/03/2012

SPECIFIED TOLERANCES ARE:
 .XX \pm .03 INCHES .X \pm .7 MM
 .XXX \pm .01 INCHES .XX \pm .25 MM
 ANGULAR: $\pm 2^\circ$

MATERIAL: NYLON 6/6,
IMPACT MODIFIED, HEAT STABILIZED
 COLOR: GREY



FASTENER DIVISION
 FITCHBURG, MA 01420 U.S.A.
 TEL: 1-800-225-5913
 FAX: 978-353-8157

DESCRIPTION: M6, 15MM OFFSET TIE, REV
 STOCK NO.: 20137-0
 REV.: A